

Material Safety Data Sheet

CONPOXY HS EPOXY GROUT A,B,C

Hard Hat Construction Supply
13407 Yorba Ave.
Chino, CA 91710

Phone: (951) 229-7321
24 hour emergency contact: CHEMTREC (800) 424-9300

SECTION I	PRODUCT IDENTIFICATION		
Trade Name	ConPoxy HS Epoxy Grout – part A		
Chemical Family	Modified Bisphenol A – Epichlorohydrin		
NFPA Ratings (Hazard ID)	Health – 2	Fire – 1	Reactivity - 0
HMIS Ratings (Hazard ID)	Health – 2	Fire – 1	Reactivity - 0
WARNING! Keep away from sparks, excessive heat, flames, welding. Irritant to skin, eyes. May be fatal if ingested or overexposed. Harmful to lungs, central nervous system, mucous membrane, possibly blood, kidneys, liver and reproductive system. Spill may create slipping hazard.			

SECTION II	INGREDIENTS, LIMITS AND TOXICOLOGICAL INFORMATION			
<i>INGREDIENT</i>	<i>Bisphenol A / Epichlorohydrin Resin</i>	<i>Nonyl Phenol</i>		
CAS#	25068-38-6	84852-15-3		
ACGIH TLV/TWA	N/A	N/A		
ACGIH TLV/STEL	N/A	N/A		
OSHA PEL/TWA	N/A	N/A		
OSHA PEL/STEL	N/A	N/A		
LD50, Oral	N/A	N/A		
LD50, Dermal	N/A	N/A		
LD50, Inhalation	N/A	N/A		
PCT by weight	70-90	0-20		

SECTION III	PHYSICAL DATA		
Physical State	Liquid	Specific Gravity	1.17
Appearance	Clear/Yellow	VOC, Calculated	N/A
Odor	Low Odor	pH	N/A
Boiling Range	N/A	Freezing Point	N/A
Vapor Pressure	0.03	Water Solubility	Negligible

SECTION IV	FIRE & EXPLOSION HAZARD DATA	
Lowest closed cup flashpoint	N/A	
OSHA flammability classification	N/A	
Lower flammable limit in air	N/A	
Flash points	N/A	
Mechanical impact explosion	N/A	
Static electricity explosion	N/A	
Extinguishing media	Dry chemical or CO ₂ is preferred	
UNUSUAL FIRE & EXPLOSION HAZARDS: KEEP CONTAINER TIGHTLY CLOSED AND ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND FLAME. NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.		
SPECIAL FIRE FIGHTING PROCEDURES: FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZELS ARE PREFERABLE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.		

SECTION V	HEALTH HAZARD DATA - Effects of overexposure – primary routes of entry		
Primary Routes of Entry	Inhalation	Skin	Ingestion
Skin contact: IRRITATION. CAN CAUSE DEFATTING OF SKIN, WHICH MAY LEAD TO DERMATITIS.			
Inhalation: IRRITATION TO NOSE AND THROAT. EXTENDED OR REPEATED EXPOSURE TO CONCENTRATIONS ABOVE THE RECOMMENDED EXPOSURE LIMITS MAY CAUSE BRAIN OR NERVOUS SYSTEM DEPRESSION, WITH SYMPTOMS SUCH AS DIZZINESS, HEADACHE OR NAUSEA AND IF CONTINUED INDEFINITELY, LOSS OF CONSCIOUSNESS, LIVER AND KIDNEY DAMAGE.			
Ingestion: MAY CAUSE MOUTH, THROAT, ESOPHAGUS AND STOMACH IRRITATION, NAUSEA, VOMITING AND DIARRHEA.			
Medical conditions that may be aggravated by exposure to this product: PREEXISTING EYE, SKIN, LIVER, KIDNEY & RESPIRATORY DISORDERS			
Emergency & First Aid procedures: IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION; FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPORS OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY.			
Other health hazards: LABORATORY ANIMALS EXPOSED TO HIGH DOSES OF XYLENE SHOWED EVIDENCE OF EFFECTS IN THE LIVER, KIDNEYS, LUNGS, CENTRAL NERVOUS SYSTEM, GI TRACT AND BLOOD FORMING ELEMENTS.			

SECTION VI	REACTIVITY DATA
Stability: STABLE HAZARDOUS POLYMERIZATION: NONE UNDER NORMAL CONDITIONS	
Conditions to avoid: ELEVATED TEMPERATURES	
Incompatibility (material to avoid) : STRONG ACIDS AND STRONG OXIDIZING AGENTS. IF THIS PRODUCT IS NOT WATER REDUCIBLE, AVOID WATER.	
Hazardous decomposition products: THERMAL DECOMPOSITION OR COMBUSTION CAN PRODUCE FUMES CONTAINING ORGANIC ACIDS, CARBON DIOXIDE, AND CARBON MONOXIDE.	

SECTION VII	SPILL OR LEAK PROCEDURES
Steps to be taken in case material is released or spilled: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES AND ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.	
Waste disposal method: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS, INCINERATE IN APPROVED FACILITY.	

SECTION VIII	SPECIAL PROTECTION INFORMATION
Respiratory Protection: DON'T BREATHE VAPORS. WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING USE OF THIS PRODUCT UNTIL VAPORS ARE EXHAUSTED, UNLESS AIR MONITORING DEMONSTRATES VAPOR LEVELS ARE BELOW APPLICABLE LIMITS, FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR RESPIRATOR USE. OBSERVE OSHA STANDARD 29CFR 1910.134.	
Ventilation: PROVIDE GENERAL CLEAN AIR DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP THE AIR CONTAMINANT CONCENTRATION BELOW THE LOWER EXPLOSION LIMIT AND BELOW CURRENT APPLICABLE EXPOSURE LIMITS. REFER TO OSHA STANDARD 1910.94.	
Protective gloves: USE SOLVENT IMPERMEABLE GLOVES TO AVOID CONTACT WITH PRODUCT.	
Eye protection: DO NOT GET IN EYES. USE SAFETY EYEWEAR WITH SPLASH GUARDS OR SIDE SHIELDS, CHEMICAL GOGGLES AND FACE SHIELDS.	
Other protective equipment: DO NOT GET ON SKIN. USE IMPERMEABLE PROTECTIVE CLOTHING. PREVENT SKIN CONTACT WITH CONTAMINATED CLOTHING. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN CONTAMINATED CLOTHING. WASH BEFORE REUSE. THOROUGHLY CLEAN CONTAMINATED SHOES. EYE BATH AND SAFETY SHOWER SHOULD BE AVAILABLE.	

SECTION IX	SPECIAL PRECAUTIONS
Precautions to be taken in handling & storage: DO NOT PRESSURIZE, CUT, WELD OR GRIND. DO NOT STORE ABOVE 120°F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP AWAY FROM HEAT, SPARKS AND FLAME. KEEP CONTAINERS CLOSED AND UPRIGHT WHEN NOT IN USE TO PREVENT LEAKAGE.	
Other precautions: DO NOT TAKE INTERNALLY. WASH HANDS AFTER USING AND BEFORE SMOKING OR EATING. EMPTIED CONTAINERS MAY RETAIN HAZARDOUS RESIDUE AND EXPLOSIVE VAPORS. KEEP AWAY FROM HEAT, SPARKS, FLAMES AND STATIC ELECTRICITY. DON'T CUT OR WELD ON OR NEAR EMPTIED CONTAINERS. FOLLOW ALL HAZARD PRECAUTIONS GIVEN IN THIS SHEET UNTIL CONTAINER IS THOROUGHLY CLEANED OR DESTROYED.	

SECTION X	SARA TITLE III INFORMATION			
<i>This product contains the following substances subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:</i>				
NAME				N/A
CAS#				
PC. WEIGHT				

SECTION XI	D.O.T. REGULATIONS (TRANSPORTATION)			
Hazard class ID number Packing group Proper shipping name Label US Domestic Ground Shipments US Domestic Ground Shipments non-bulk (in containers 119 gallons or less)	NOT REGULATED BY THE D.O.T.			
Cross Border Transport (ADR/RID)				
ADR/RID Class Danger Code (Kemler) UN Number Packing Group Description	N/A			
Marine Transport (IMDG)				
IMDG Class UN Number Label Packing Group EMS Number Marine Pollutant Proper Shipping Name	N/A			
Air Transport (ICAO-TI and IATA-DGR)				
ICAO/IATA Class UN Number Label Packing Group Proper Shipping Name	N/A			

DISCLAIMER AND LIMITATION OF LIABILITY
The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of the knowledge of SpecChem; however, SpecChem makes no warranty whatsoever, expressed or implied, of MERCHANTABILITY or FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained from the use thereof. SpecChem assumes no responsibility for injury to recipient, to third persons or to any property. Recipient assumes all risk.

Material Safety Data Sheet

CONPOXY HS EPOXY A,B,C

Hard Hat Construction Supply
13407 Yorba Ave.
Chino, CA 91710

Phone: (951) 229-7321
24 hour emergency contact: CHEMTREC (800) 424-9300

SECTION I	PRODUCT IDENTIFICATION		
Trade Name	ConPoxy HS Epoxy Grout – part B		
Chemical Family	Modified Amines		
NFPA Ratings (Hazard ID)	Health – 2	Fire – 1	Reactivity - 0
HMIS Ratings (Hazard ID)	Health – 2	Fire – 1	Reactivity - 0
WARNING! Keep away from sparks, excessive heat, flames, welding. Irritant to skin, eyes. May be fatal if ingested or overexposed. Harmful to lungs, central nervous system, mucous membrane, possibly blood, kidneys, liver and reproductive system. Spill may create slipping hazard.			

SECTION II	INGREDIENTS, LIMITS AND TOXICOLOGICAL INFORMATION			
INGREDIENT	<i>N-Amino Ethyl Piperazine</i>	<i>Aliphatic Polyamido Amine Modified</i>	<i>Nonyl Phenol</i>	
CAS#	140-31-8	N/A	84852-15-3	
ACGIH TLV/TWA	N/A	N/A	N/A	
ACGIH TLV/STEL	N/A	N/A	N/A	
OSHA PEL/TWA	N/A	N/A	N/A	
OSHA PEL/STEL	N/A	N/A	N/A	
LD50, Oral	N/A	N/A	N/A	
LD50, Dermal	N/A	N/A	N/A	
LD50, Inhalation	N/A	N/A	N/A	
PCT by weight	0-30	0-50	0-50	

SECTION III	PHYSICAL DATA		
Physical State	Liquid	Specific Gravity	0.96
Appearance	Mobile Amber Liquid	VOC, Calculated	N/A
Odor	Ammoniacal / Fishy	pH	Alkaline
Boiling Range	N/A	Freezing Point	N/A
Vapor Pressure	<1	Water Solubility	Negligible

SECTION IV	FIRE & EXPLOSION HAZARD DATA
Lowest closed cup flashpoint	Over 212°F
OSHA flammability classification	N/A
Lower flammable limit in air	N/A
Flash points	Over 212°F
Mechanical impact explosion	N/A
Static electricity explosion	N/A
Extinguishing media	Dry chemical or CO ₂ is preferred
UNUSUAL FIRE & EXPLOSION HAZARDS: KEEP CONTAINER TIGHTLY CLOSED AND ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND FLAME. NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.	
SPECIAL FIRE FIGHTING PROCEDURES: FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZELS ARE PREFERABLE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.	

SECTION V	HEALTH HAZARD DATA - Effects of overexposure – primary routes of entry		
Primary Routes of Entry	Inhalation	Skin	Ingestion
Skin contact: IRRITATION. CAN CAUSE DEFATTING OF SKIN, WHICH MAY LEAD TO DERMATITIS.			
Inhalation: IRRITATION TO NOSE AND THROAT. EXTENDED OR REPEATED EXPOSURE TO CONCENTRATIONS ABOVE THE RECOMMENDED EXPOSURE LIMITS MAY CAUSE BRAIN OR NERVOUS SYSTEM DEPRESSION, WITH SYMPTOMS SUCH AS DIZZINESS, HEADACHE OR NAUSEA AND IF CONTINUED INDEFINITELY, LOSS OF CONSCIOUSNESS, LIVER AND KIDNEY DAMAGE.			
Ingestion: MAY CAUSE MOUTH, THROAT, ESOPHAGUS AND STOMACH IRRITATION, NAUSEA, VOMITING AND DIARRHEA.			
Medical conditions that may be aggravated by exposure to this product: PREEXISTING EYE, SKIN, LIVER, KIDNEY & RESPIRATORY DISORDERS			
Emergency & First Aid procedures: IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION; FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPORS OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY.			
Other health hazards: LABORATORY ANIMALS EXPOSED TO HIGH DOSES OF XYLENE SHOWED EVIDENCE OF EFFECTS IN THE LIVER, KIDNEYS, LUNGS, CENTRAL NERVOUS SYSTEM, GI TRACT AND BLOOD FORMING ELEMENTS.			

SECTION VI	REACTIVITY DATA
Stability: STABLE HAZARDOUS POLYMERIZATION: NONE UNDER NORMAL CONDITIONS	
Conditions to avoid: ELEVATED TEMPERATURES	
Incompatibility (material to avoid) : STRONG ACIDS AND STRONG OXIDIZING AGENTS. IF THIS PRODUCT IS NOT WATER REDUCIBLE, AVOID WATER.	
Hazardous decomposition products: THERMAL DECOMPOSITION OR COMBUSTION CAN PRODUCE FUMES CONTAINING ORGANIC ACIDS, CARBON DIOXIDE, AND CARBON MONOXIDE.	

SECTION VII	SPILL OR LEAK PROCEDURES
Steps to be taken in case material is released or spilled: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES AND ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.	
Waste disposal method: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS, INCINERATE IN APPROVED FACILITY.	

SECTION VIII	SPECIAL PROTECTION INFORMATION
Respiratory Protection: DON'T BREATHE VAPORS. WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING USE OF THIS PRODUCT UNTIL VAPORS ARE EXHAUSTED, UNLESS AIR MONITORING DEMONSTRATES VAPOR LEVELS ARE BELOW APPLICABLE LIMITS, FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR RESPIRATOR USE. OBSERVE OSHA STANDARD 29CFR 1910.134.	
Ventilation: PROVIDE GENERAL CLEAN AIR DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP THE AIR CONTAMINANT CONCENTRATION BELOW THE LOWER EXPLOSION LIMIT AND BELOW CURRENT APPLICABLE EXPOSURE LIMITS. REFER TO OSHA STANDARD 1910.94.	
Protective gloves: USE SOLVENT IMPERMEABLE GLOVES TO AVOID CONTACT WITH PRODUCT.	
Eye protection: DO NOT GET IN EYES. USE SAFETY EYEWEAR WITH SPLASH GUARDS OR SIDE SHIELDS, CHEMICAL GOGGLES AND FACE SHIELDS.	
Other protective equipment: DO NOT GET ON SKIN. USE IMPERMEABLE PROTECTIVE CLOTHING. PREVENT SKIN CONTACT WITH CONTAMINATED CLOTHING. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN CONTAMINATED CLOTHING. WASH BEFORE REUSE. THOROUGHLY CLEAN CONTAMINATED SHOES. EYE BATH AND SAFETY SHOWER SHOULD BE AVAILABLE.	

SECTION IX	SPECIAL PRECAUTIONS
Precautions to be taken in handling & storage: DO NOT PRESSURIZE, CUT, WELD OR GRIND. DO NOT STORE ABOVE 120°F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP AWAY FROM HEAT, SPARKS AND FLAME. KEEP CONTAINERS CLOSED AND UPRIGHT WHEN NOT IN USE TO PREVENT LEAKAGE.	
Other precautions: DO NOT TAKE INTERNALLY. WASH HANDS AFTER USING AND BEFORE SMOKING OR EATING. EMPTIED CONTAINERS MAY RETAIN HAZARDOUS RESIDUE AND EXPLOSIVE VAPORS. KEEP AWAY FROM HEAT, SPARKS, FLAMES AND STATIC ELECTRICITY. DON'T CUT OR WELD ON OR NEAR EMPTIED CONTAINERS. FOLLOW ALL HAZARD PRECAUTIONS GIVEN IN THIS SHEET UNTIL CONTAINER IS THOROUGHLY CLEANED OR DESTROYED.	

SECTION X		SARA TITLE III INFORMATION		
<i>This product contains the following substances subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:</i>				
				N/A ☒
NAME				
CAS#				
PC. WEIGHT				

SECTION XI		D.O.T. REGULATIONS (TRANSPORTATION)		
Hazard class	8			
ID number	UN 2735			
Packing group	III			
Proper shipping name	Amines, Liquid, Corrosive NOS (Aminopropyldiethanolamine)			
Label	8			
US Domestic Ground Shipments	Corrosive Liquid NOS			
US Domestic Ground Shipments non-bulk (in containers 119 gallons or less)	Corrosive Liquid NOS			
Cross Border Transport (ADR/RID)				
ADR/RID Class	8 Corrosive Substances			
Danger Code (Kemler)	8			
UN Number	2735			
Packing Group	III			
Description	2735 Amines, Corrosive Liquid NOS			
Marine Transport (IMDG)				
IMDG Class	8			
UN Number	2735			
Label	8			
Packing Group	III			
EMS Number	F-A, S-B			
Marine Pollutant	No			
Proper Shipping Name	Amines, Corrosive Liquid NOS			
Air Transport (ICAO-TI and IATA-DGR)				
ICAO/IATA Class	8			
UN Number	2735			
Label	8			
Packing Group	III			
Proper Shipping Name	Amines, Corrosive Liquid NOS			

DISCLAIMER AND LIMITATION OF LIABILITY	
<p>The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of the knowledge of SpecChem; however, SpecChem makes no warranty whatsoever, expressed or implied, of MERCHANTABILITY or FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained from the use thereof. SpecChem assumes no responsibility for injury to recipient, to third persons or to any property. Recipient assumes all risk.</p>	

Material Safety Data Sheet

CONPOXY HS EPOXY GROUT A,B,C

Hard Hat Construction Supply
13407 Yorba Ave.
Chino, CA 91710

Phone: (951) 229-7321
24 hour emergency contact: CHEMTREC (800) 424-9300

SECTION I		PRODUCT IDENTIFICATION		
Trade Name	Specpoxy Grout – part C			
Chemical Family	Cementitious Product			
NFPA Ratings (Hazard ID)	Health – 1	Fire – 0	Reactivity - 0	
HMIS Ratings (Hazard ID)	Health – 1	Fire – 0	Reactivity - 0	
WARNING! Irritant to skin, eyes. May be harmful to respiratory system. Contains silica, sand, cement.				

SECTION II		INGREDIENTS, LIMITS AND TOXICOLOGICAL INFORMATION			
INGREDIENT	Portland Cement	Silica Crystalline Quartz	Aluminum Cement	Calcium Sulfate	
CAS#	65997-15-1	7631-89-9	65997-16-2	13397-24-5	
ACGIH TLV/TWA	5 ppm	0.1 ppm	5 ppm	5 ppm	
ACGIH TLV/STEL	N/A	N/A	N/A	N/A	
OSHA PEL/TWA	5 ppm	0.1 ppm	5 ppm	5 ppm	
OSHA PEL/STEL	N/A	N/A	N/A	N/A	
LD50, Oral	N/A	N/A	N/A	N/A	
LD50, Dermal	N/A	N/A	N/A	N/A	
LD50, Inhalation	N/A	N/A	N/A	N/A	
PCT by weight	30-70	70-30	0-70	0-15	

SECTION III		PHYSICAL DATA		
Physical State	Powder	Specific Gravity	2.7 – 3.0	
Appearance	Gray	VOC, Calculated	N/A	
Odor	Low or no odor	pH	12 when mixed with water	
Boiling Range	N/A	Freezing Point	N/A	
Vapor Pressure	N/A	Water Solubility	Negligible	

SECTION IV		FIRE & EXPLOSION HAZARD DATA	
Lowest closed cup flashpoint	N/A		
OSHA flammability classification	N/A		
Lower flammable limit in air	N/A		
Flash points	N/A		
Mechanical impact explosion	N/A		
Static electricity explosion	N/A		
Extinguishing media	Use extinguishing agent suitable for type of surrounding fire & structure.		
UNUSUAL FIRE & EXPLOSION HAZARDS:	N/A		
SPECIAL FIRE FIGHTING PROCEDURES:	N/A		

SECTION V	HEALTH HAZARD DATA - Effects of overexposure – primary routes of entry		
Primary Routes of Entry	Inhalation	Skin	Ingestion
Skin contact: IRRITATION. CAN CAUSE DEFATTING OF SKIN, WHICH MAY LEAD TO DERMATITIS.			
Inhalation: DRY MATERIAL: NUISANCE DUST MAY CAUSE REVERSIBLE RESPIRATORY PROBLEMS; OFTEN NON-PROTECTING EXPOSURE OVER TLV MAY RESULT IN SILICONS.			
Ingestion: N/A			
Medical conditions that may be aggravated by exposure to this product: PREEXISTING EYE, SKIN, LIVER, KIDNEY & RESPIRATORY DISORDERS			
Emergency & First Aid procedures: IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION; FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPORS OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY.			
Other health hazards: N/A			

SECTION VI	REACTIVITY DATA
Stability: STABLE: NONE UNDER NORMAL CONDITIONS	
Conditions to avoid: UPON DIRECT CONTACT WITH WATER, MATERIAL WILL HARDEN.	
Incompatibility (material to avoid) : N/A	
Hazardous decomposition products: N/A	

SECTION VII	SPILL OR LEAK PROCEDURES
Steps to be taken in case material is released or spilled: USE DRY CLEAN UP METHOD THAT DOES NOT DISPENSE MATERIAL INTO THE AIR. DO NOT BREATHE DUST. AVOID CONTACT WITH EYES.	
Waste disposal method: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS, INCINERATE IN APPROVED FACILITY.	

SECTION VIII	SPECIAL PROTECTION INFORMATION
Respiratory Protection: USE OSHA, MSHA OR NIOSH APPROVED DUST RESPIRATORS.	
Ventilation: PROVIDE GENERAL CLEAN AIR DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP THE AIR CONTAMINANT CONCENTRATION BELOW THE LOWER EXPLOSION LIMIT AND BELOW CURRENT APPLICABLE EXPOSURE LIMITS.	
Protective gloves: USE ANY RUBBER GLOVES TO AVOID CONTACT WITH PRODUCT.	
Eye protection: DO NOT GET IN EYES. USE SAFETY EYEWEAR.	
Other protective equipment: USE IMPERMEABLE PROTECTIVE CLOTHING. PREVENT SKIN CONTACT WITH CONTAMINATED CLOTHING. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN CONTAMINATED CLOTHING.	

SECTION IX	SPECIAL PRECAUTIONS
Precautions to be taken in handling & storage: KEEP MATERIAL DRY UNTIL USED. HIGH HUMIDITY OR MOISTURE WILL CAUSE PREMATURE HARDENING OF MATERIAL.	
Other precautions: DO NOT TAKE INTERNALLY. WASH HANDS AFTER USING AND BEFORE SMOKING OR EATING. EXPOSURE TO AIRBORNE CRYSTALLINE SILICA SHALL NOT EXCEED 8 HOURS A DAY. SEE 29CFR 1910.1000 TABLE Z-3. SEE ALSO OSHA 29 CFR 1910.134; ANSI Z.88.2; NIOSH POCKET GUIDE TO CHEMICAL HAZARD.	

SECTION X	SARA TITLE III INFORMATION		
<i>This product contains the following substances subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:</i>			
NAME			N/A ☒
CAS#			
PC. WEIGHT			

SECTION XI	D.O.T. REGULATIONS (TRANSPORTATION)
Hazard class ID number Packing group Proper shipping name Label US Domestic Ground Shipments US Domestic Ground Shipments non-bulk (in containers 119 gallons or less)	NOT REGULATED BY D.O.T.
Cross Border Transport (ADR/RID)	
ADR/RID Class Danger Code (Kemler) UN Number Packing Group Description	N/A
Marine Transport (IMDG)	
IMDG Class UN Number Label Packing Group EMS Number Marine Pollutant Proper Shipping Name	N/A No
Air Transport (ICAO-TI and IATA-DGR)	
ICAO/IATA Class UN Number Label Packing Group Proper Shipping Name	N/A

DISCLAIMER AND LIMITATION OF LIABILITY

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of the knowledge of SpecChem; however, SpecChem makes no warranty whatsoever, expressed or implied, of MERCHANTABILITY or FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained from the use thereof. SpecChem assumes no responsibility for injury to recipient, to third persons or to any property. Recipient assumes all risk.