

# AcrylCure Cure/Seal 18%

Water-based cure & seal (ASTM C-309 compliant)

## DESCRIPTION

ACRYLCURE CURE/SEAL 18% is a water-based, non-yellowing, VOC compliant acrylic polymer engineered to cure, seal, harden, and dustproof freshly placed concrete and improve the wearability and durability of aged concrete surfaces. May contribute to LEED credits.

## FEATURES/BENEFITS

- Provides a tough glossy film that is resistant to abrasion and common staining materials
- Prevents the adhesion of cementitious droppings and the penetration of most oils and greases
- Reduces maintenance and clean-up costs
- Cleans and brightens floors
- May be recoated prior to occupancy for a glossy final finish
- May be recoated at any time without stripping the prior application

## SPECIFICATIONS/COMPLIANCE

Meets ASTM C-309, Type I, Class A and B  
 ACRYLCURE CURE/SEAL 18% meets V.O.C. emission requirements for curing and sealing compounds (Actual VOC = 98 g/L).

## APPLICATION

Coverage: Ready to use. Do not dilute. Apply with a sprayer, brush, roller or lambs wool applicator. Spraying or a lambs wool applicator generally will provide superior results. Avoid puddles. Apply in accordance with recommended coverage rates.

Curing: 200 sq ft / gal  
 Dustproofing and Sealing: 200 – 400 sq ft / gal  
 Aged concrete: 200 – 400 sq ft / gal

For dustproofing and sealing benefits, apply two coats at 300 sq ft / gal. On broom or rough finished concrete, double the coverage rate. Coverage may vary due to porosity and conditions of the concrete. Application temperature above 40° & rising is recommended.

**New Concrete:** ACRYLCURE CURE/SEAL 18% should be applied as soon as the surface water has disappeared and the concrete surface will not be marred by the walking applicator. At this point, apply in a uniform coat. For a superior finish and added curing and sealing protection, apply a second coat at 400 sq ft / gal.

**Existing Concrete:** Concrete surface must be clean, dry or damp and free of all stains, oil, grease, dirt, and incompatible coatings prior to application.

ACRYLCURE CURE/SEAL 18% can be used on colored concrete and will renovate existing concrete, brick or terrazzo floors. These surfaces will be brighter and easier to clean and maintain.

ACRYLCURE CURE/SEAL 18% is compatible with most carpets, tile and floor covering adhesives. Due to the wide variation in the chemistry of adhesives, a test section is always recommended.

## CLEAN UP

Application equipment can be cleaned with water if product has not dried. Once product dries, xylene or other approved solvents should be used.

## PACKAGING

275 gallon totes  
 55 gallon drums  
 5 gallon pails

## STORAGE/SHELF LIFE

Shelf life of ACRYLCURE CURE/SEAL 18% in the original tightly closed containers is one year from the date of manufacture. Do not allow the accumulation of water, dirt, or other contaminants.

## TYPICAL TEST DATA

Moisture Retention (ASTM C-309) at 200 sq ft/gal (Kg/m <sup>2</sup> )	
Test Result	Required
0.39 Kg/m <sup>2</sup>	0.55 Kg/m <sup>2</sup>

## LIMITATIONS/PRECAUTIONS

Does not provide a base for cementitious materials. Not for use in fountains or pools.

When used over colored concrete, ACRYLCURE CURE/SEAL 18% may enhance color variation or imperfections. Prepare a test panel to ensure acceptable results.

Rubber wheeled vehicles may leave black marks.

Protect from freezing.

Contact Technical Services for complete application instructions and limitations.

Additional precautions, safety and first aid information are contained in the Material Safety Data Sheet.

Application temperature above 40° & rising is recommended.

## WARRANTY

### NOTICE-READ CAREFULLY CONDITIONS OF SALE

The manufacturer offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of The manufacturer. No other representative of or for The manufacturer is authorized to grant any warranty or to waive limitation of liability set forth below.

### WARRANTY LIMITATION

The manufacturer warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, The manufacturer will replace the defective product with new product without charge to the purchaser. The manufacturer makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

### INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.



13407 Yorba Ave.  
 Chino, CA 91710

hardhatconstructionsupply.com