

Eco Best Form Release

100% Biodegradable Water Based Form Release Agent

DESCRIPTION

ECO BEST FORM RELEASE is a 100% natural organic chemically reactive release agent. Ideal for sensitive environmental situations such as bridge formwork over rivers and streams or potable water reservoirs. ECO BEST FORM RELEASE provides quick, easy release and leaves an architectural bondable concrete surface.

FEATURES/BENEFITS

- Organic/Biodegradable
- No petroleum distillates
- Environmentally friendly
- VOC compliant/Odorless
- Ready to use
- Chemically reactive/Non-staining

SPECIFICATIONS/COMPLIANCE

Tested and certified to the performance requirements of NSF/ANSI 61
 Corps of Engineers CEGS-03300, Section 10.8 Form Coating; CE-204, Section 7.10 Navy Dock and Piers 56359
 V.O.C. Compliant (0 grams/liter)
 100% Biodegradable

APPLICATION

Stir ECO BEST FORM RELEASE slowly and thoroughly before each use using slow speed mixing equipment.

ECO BEST FORM RELEASE should be applied with a sprayer, brush or roller in a thin uniform film. No special application equipment is necessary, but a spray application is the most practical. Ponding or puddling is to be avoided. Specific application rates:

Steel, Plastic, Fiberglass	1,500 sq ft/gal
Aluminum, HDO Plywood	1,500 sq ft/gal
Elastometric Form Liners	1,500 sq ft/gal
MDO Plywood	1,000 sq ft/gal
Urethane Coated Plywood	1,000 sq ft/gal
Coated Paper Forms	1,000 sq ft/gal
Dimensional Lumber	750 sq ft/gal
Rough Sawn Lumber	750 sq ft/gal
Striated Plywood	750 sq ft/gal

CLEAN UP

Sprayers and other application equipment can be cleaned with water.

PACKAGING

- 275 gallon totes
- 55 gallon drums
- 5 gallon pails

PHYSICAL PROPERTIES

Finished Appearance:	Clear
Color:	Milky White
Flash Point:	None
VOC Content:	0 g/L

STORAGE/SHELF LIFE

Shelf life of ECO BEST FORM RELEASE in the original tightly closed containers is one year from date of manufactured date.

LIMITATIONS/PRECAUTIONS

For subsequent coatings over concrete, follow recommended application procedures by paint and coating manufacturers. When any material is to be applied on top of the concrete, follow the application instructions of the manufacturer. Protect from freezing.

DO NOT CUT OR WELD CONTAINER INDUSTRIAL USE ONLY

Additional precautions, safety information and first aid are contained in the Material Safety Data Sheet.

WARRANTY

NOTICE-READ CAREFULLY CONDITIONS OF SALE

The manufacturer offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of The manufacturer. No other representative of or for The manufacturer is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

The manufacturer warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, The manufacturer will replace the defective product with new product without charge to the purchaser. The manufacturer makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.



13407 Yorba Ave.
Chino, CA 91710

hardhatconstructionsupply.com